

Application No. 10/662,950
Response to Office Action
Date: August 23, 2006

Attorney Docket No. YO896-0213R5

VIA FACSIMILE TRANSMISSION - Official
To Fax Number 571-273-8300

RECEIVED
CENTRAL FAX CENTER
AUG 23 2006

In The Claims:

Please add new claims 38 – 54.

The following listing of claims will replace all prior versions of claims in the application.

Listing of Claims

Claims 1-17 (cancelled)

Claim 18 (previously presented): A method for maintaining information in a Radio Frequency transponder, said information being retained during a period when no power is supplied to said transponder, the method comprising the steps of:

- (a) applying power to said transponder from an external field;
- (b) after removal of the power applied to said transponder, utilizing stored energy from the applied power to retain the information during the period when no power is applied to said transponder; and
- (c) utilizing the retained information to restore the transponder to a state represented by the retained information when the transponder is again subjected to an external field even after a substantial time interval with no power from an external field.

Claim 19 (previously presented): The method of claim 18, wherein the information is retained in an auxiliary volatile storage by the stored energy from the applied power for a substantial time interval of at least one second.

Claim 20 (previously presented): The method of claim 19, wherein the energy required to retain information in the auxiliary volatile storage is stored in an auxiliary charge storage which substantially only supplies energy to said auxiliary volatile storage.

Application No. 10/662,950
Response to Office Action
Date: August 23, 2006

Attorney Docket No. YO896-0213R5

VIA FACSIMILE TRANSMISSION – Official

To Fax Number 571-273-8300

Claim 21 (previously presented): The method of claim 18, wherein power is applied to the transponder at intervals such that the stored energy should remain adequate to retain said information, for the time intervals between successive applications of power, when a multitag identification operation is being carried out including said transponder.

Claim 22 (previously presented): The method of claim 18, wherein the information is stored in an auxiliary volatile storage for a substantial time period after removal of power applied to the transponder, and the stored information is transferred to a different section of the transponder when power is again applied to said transponder, the energy required to retain information in the auxiliary volatile storage being stored in an auxiliary charge storage device which does not supply energy to the different section of the transponder.

Claim 23 (previously presented): The method of claim 18, wherein the energy required to retain information in the auxiliary volatile storage is stored in an auxiliary charge storage which substantially only supplies energy to said auxiliary volatile storage.

Claim 24 (previously presented): The method of claim 18, wherein the information is retained in an auxiliary volatile storage by the stored energy from the applied power for a substantial time interval of at least a plurality of seconds.

Claim 25 (previously presented): The method of claim 24, wherein the information is stored in an auxiliary volatile storage for a substantial time period after removal of power applied to the transponder, and the stored information is transferred to a different section of the transponder when power is again applied to said transponder, the energy required to retain information in the auxiliary volatile storage being stored in an auxiliary charge storage device which does not supply energy to the different section of the transponder.

Claim 26 (previously presented): An RF tag comprising:

- (a) a tag antenna for receiving RF power and modulated RF information signals sent to said RF tag by a base station;

Application No. 10/662,950
Response to Office Action
Date: August 23, 2006

Attorney Docket No. YO896-0213R5

VIA FACSIMILE TRANSMISSION - Official

To Fax Number 571-273-8300

(b) a first tag voltage rectification circuit coupled to said tag antenna for receiving said RF power from said tag antenna and for providing power to the electronic components of said RF tag, said electronic components receiving said power only from said first tag voltage rectification circuit;

(c) a main memory;

(d) a volatile auxiliary memory for storing state information in the absence of a received RF power signal; and

(e) an auxiliary power capacitor for storing energy while the antenna is receiving RF power, for energizing said volatile auxiliary memory, where said auxiliary power capacitor retains sufficient energy to power said volatile auxiliary memory so as to retain the stored state information for a substantial period of time of at least one second after said RF power to said RF tag is removed.

Claim 27 (previously presented): The RF tag of claim 26, further comprising a second tag voltage rectification circuit coupled to said tag antenna for receiving said RF power from said tag antenna, said electronic components receiving said power only from said first tag voltage rectification circuit, and said auxiliary capacitor receiving power only from said second tag voltage rectification circuit.

Claim 28 (previously presented): The RF tag of claim 27, wherein said second tag voltage rectification circuit comprises a PFET transistor.

Claim 29 (previously presented): A method of effecting a multi-tag identification operation, comprising the steps of:

(a) providing RF energy to a plurality of RF tags disposed in a field region thereof to activate at least one of said plurality of RF tags, wherein at least said one RF tag includes a power storage device, and a volatile information retaining device;

(b) supplying energy to said power storage device, whereby said power storage device can power said volatile information retaining device for a substantial time interval when said one RF tag is de-activated; and

Application No. 10/662,950
Response to Office Action
Date: August 23, 2006

Attorney Docket No. YO896-0213R5

VIA FACSIMILE TRANSMISSION – Official

To Fax Number 571-273-8300

(c) utilizing the power storage device to retain state information comprising information that said one RF tag has been identified.

Claim 30 (previously presented): The method of claim 29, wherein the information is retained in the volatile information retaining device by the stored energy of the power storage device for a time interval of at least one second.

Claim 31 (previously presented): The method of claim 29, wherein the energy required to retain information in said volatile information retaining device is stored in the power storage device which substantially only supplies energy to said volatile information retaining device.

Claim 32 (previously presented): The method of claim 29, wherein power is applied to the transponder at intervals such that the stored energy of the power storage device should remain adequate to retain said information, for the time intervals between successive applications of power, when a multitag identification operation is being carried out including said transponder.

Claim 33 (previously presented): The method of claim 29, wherein the state information is stored in said volatile information retaining device for a substantial time period after removal of power applied to the transponder, and the stored state information is transferred to a different section of the transponder when power is again applied to said transponder, the energy required to retain the state information in said volatile information retaining device being stored in the power storage device which does not supply energy to the different section of the transponder.

Claim 34 (previously presented): The method of claim 29, wherein the energy required to retain the state information in said volatile information retaining device is stored in the power storage device which substantially only supplies energy to said volatile information retaining device.

Application No. 10/662,950
Response to Office Action
Date: August 23, 2006

Attorney Docket No. YO896-0213R5

VIA FACSIMILE TRANSMISSION – Official
To Fax Number 571-273-8300

Claim 35 (previously presented): The method of claim 29, wherein the information is retained in the volatile information retaining device by the power storage device for a substantial time interval of at least a plurality of seconds.

Claim 36 (previously presented): An RF tag comprising:

- (a) a tag antenna for receiving RF power and modulated RF information signals sent to said RF tag by a base station;
- (b) a tag voltage rectification circuit coupled to said tag antenna for receiving said RF power from said tag antenna and for providing power to the electronic components of said RF tag;
- (c) a main memory;
- (d) a volatile auxiliary memory for storing state information upon interruption of the received RF power signal;
- (e) an auxiliary power capacitor for storing energy while the antenna is receiving RF power, for energizing said volatile auxiliary memory, where said auxiliary power capacitor retains sufficient energy to power said volatile auxiliary memory so as to retain the stored state information for a substantial period of time after said RF power to said RF tag is removed; and
- (f) a circuit for transferring the stored state information from the volatile auxiliary memory to the main memory when RF power is again received by the tag voltage rectification circuit.

Claim 37 (previously presented): The RF tag of claim 36, wherein the auxiliary power capacitor retains sufficient energy to power said volatile auxiliary memory so as to retain the stored state information for a substantial period of time of at least one second after said RF power to said RF tag is removed.

Application No. 10/662,950
Response to Office Action
Date: August 23, 2006

Attorney Docket No. YO896-0213R5

VIA FACSIMILE TRANSMISSION – Official

To Fax Number 571-273-8300

Claim 38 (new): A method of effecting a multitag identification operation, comprising the steps of:

(a) providing RF energy to a field region containing a plurality of RF tags to activate at least one of said plurality of RF tags, wherein at least said one RF tag includes a volatile information retaining device comprising a power storage device, and

(b) supplying energy to said power storage device of said one tag during receipt of adequate RF energy to activate said one tag, whereby said volatile information retaining device of said one tag retains information for a substantial time interval even when the supply of said RF energy is present in the field region but is no longer adequate to activate said one tag; and

(c) utilizing the volatile information retaining device to retain information that said one RF tag has been identified during a multitag identification operation.

Claim 39 (new): The method of claim 38, wherein the information is retained in the volatile information retaining device by the stored energy of the power storage device for a time interval of at least one second.

Claim 40 (new): The method of claim 38, wherein the energy required to retain information in said volatile information retaining device is stored in the power storage device which substantially only supplies energy to said volatile information retaining device.

Claim 41 (new): The method of claim 38, wherein RF energy is applied to said one tag at intervals during a multitag identification operation such that the stored energy of the power storage device should remain adequate to retain said information during the time that the multitag identification operation is being carried out.

Claim 42 (new): The method of claim 38, wherein state information is stored in said volatile information retaining device for a substantial time period while adequate RF energy is not being received by said one tag, and the stored state information is

Application No. 10/662,950
Response to Office Action
Date: August 23, 2006

Attorney Docket No. YO896-0213R5

VIA FACSIMILE TRANSMISSION – Official

To Fax Number 571-273-8300

transferred to a different section of said one tag when adequate RF energy is again applied to said one tag, the energy required to retain the state information in said volatile information retaining device being stored in the power storage device which does not supply energy to the different section of said one tag.

Claim 43 (new): The method of claim 42, wherein the energy required to retain the state information in said volatile information retaining device is stored in the power storage device which substantially only supplies energy to said volatile information retaining device.

Claim 44 (new): The method of claim 38, wherein the information is retained in the volatile information retaining device by the power storage device for a substantial time interval of one second or so.

Claim 45 (new): The method of claim 38, wherein the energy required to retain the information in said volatile information retaining device is stored in the power storage device which substantially only supplies energy to a few transistors.

Claim 46 (new): The method of claim 38, wherein the information is retained in the volatile information retaining device by the power storage device for a substantial time interval of a plurality of seconds.

Claim 47 (new): The method of claim 38, wherein the supplying of RF energy to said field region changes a characteristic of such RF energy during the multitag identification operation such that adequate RF energy to activate said one tag, is only available at intervals when RF energy of a given characteristic is being supplied, whereby said volatile information retaining device of said one tag retains information for a substantial time interval even when the supply of said RF energy is present in the field region but is not of a characteristic to adequately activate said one tag;

Application No. 10/662,950
Response to Office Action
Date: August 23, 2006

Attorney Docket No. YO896-0213R5

VIA FACSIMILE TRANSMISSION – Official
To Fax Number 571-273-8300

Claim 48 (new): The method of claim 47, wherein the supplying of RF energy to said field region changes in the polarization of such RF energy such that adequate RF energy to activate said one tag, is only available at intervals where a given polarization of such RF energy is being supplied.

Claim 49 (new): The method of claim 47, wherein the supplying of RF energy to said field region changes in the frequency of such RF energy and adequate RF energy to activate said one tag, is not available during sending of such RF energy at a given frequency.

Claim 50 (new): The method of effecting a multitag identification operation, which comprises:

- (a) sending energizing RF energy to RF tags in a field region during a multitag identification operation,
- (b) for certain tags receiving sufficient RF energy, utilizing stored energy to maintain information that such tags have been identified during a substantial time interval while RF energy is being sent to the field region but adequate RF energy is not being received by the certain tags
- (c) such that the certain tags retain the information that such tags have been identified during the multitag identification operation.

Claim 51 (new): The method of claim 50, wherein the stored energy required to retain the information is stored in a power storage device which substantially only supplies energy to retain said information..

Claim 52 (new): The method of claim 50 where the certain tags will automatically effectively lose said information at the end of the multitag identification operation when RF energy is not received before the end of said substantial time interval.

Application No. 10/662,950
Response to Office Action
Date: August 23, 2006

Attorney Docket No. YO896-0213R5

VIA FACSIMILE TRANSMISSION – Official

To Fax Number 571-273-8300

Claim 53 (new): The method of claim 50, wherein the substantial time interval has a duration of one second or so.

Claim 54 (new): The method of claim 50, wherein the energy required to retain the information is stored in a power storage device which substantially only supplies energy to a few transistors.